

Canon



**imagePROGRAF
TA-20 MFP L24ei**



imagePROGRAF TA-20 MFP L24ei

SPECIFICATIONS

PRINTER SPECIFICATIONS

Print Head
PF-06

Technology
FINE (Photolithography Inkjet Nozzle Engineering)

Print Resolution (Max.)
2400 x 1200 dpi

Line Accuracy*
±0.1% or Less

Number of Nozzles
Matte Black: 5,120 Nozzles
Other Colors: 2,560 Nozzles per Color

Droplet Size
Minimum 5 Picoliter

Ink Type
Pigment: Matte Black (MBK), Cyan (C), Magenta (M), Yellow (Y), Black (BK)

Ink Tank
Shipped with Printer: (2) MBK, BK, C, M, Y (55 ml)
Replacement: PFI-030 (55 ml)

Ink Supply Method
Tubing System with Sub-tanks for Continuous Ink Supply

Nozzle Recovery System
Non-firing Nozzle Detection and Compensation

Printer Controller
L-COA PRO

Printer RAM
2 GB

Media Feed
Roll Feed: One Roll, Top-loading, Front Output
Cut Sheet: Top-loading, Front Output

Media Width
Roll Feed: 8"-24"(203 mm -610 mm)
Cut Sheet: 8"-24"(203 mm -432 mm)

Printable Margins
Roll Feed: All Sides: 3 mm or 0" for Borderless
Cut Sheet: Top: 3 mm; Bottom: 20 mm; Side: 3 mm
Borderless Printing Widths (Roll Media Only)
8" - 24"

Media Cutter
Rotary Cutter

Media Thickness
0.07 - 0.8 mm

Media Core Sizes
2" and 3" [Optional 2"/3" Roll Holder Set (RH2-28) is needed to support 3" media cores]

Maximum Roll Outer Diameter
5.9" (150 mm)

Printing Software Utilities
Accounting Manager, Canon Print Service, Device Management Console, Direct Print & Share, Free Layout Plus, imagePROGRAF Printer Driver for Windows*/Mac*, Media Configuration Tool, PosterArtist Lite for Windows, Canon PRINT Inkjet Selphy, Easy-Photo PrintEditor,* Optimized Driver for AutoCAD, Free Layout

Operating System
Windows 7 (32/64 bit), Windows 8.1 (32/64 bit), Windows 10 (32/64 bit), Windows Server 2008 R2, (32/64 bit), Windows Server 2012 (64 bit), Windows Server 2012 R2 (64 bit), Windows Server 2016 (64 bit), Macintosh OS X v10.10.5-v10.12x

Print Language
Printer: SGRaster, HP-GL/2, HP RTL, JPEG

Interface
Standard (Built-in): USB 2.0 Hi-Speed, 10/100/ 1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n)■

Acoustic Noise
Operation: 42 dB (A)
Standby: 35 dB (A) or Less
Acoustic Power: 5.3 Bels

Power Supply
AC 100-240V (50-60 Hz)

Power Consumption
Maximum: 52 W or Less
Standby: 3.6 W or Less
Power Off: 0.3 W or Less (Executive Order Compliant)

Certifications
Electrical Safety Regulations
C TUVus (U.S.A.)
Electromagnetic Interface Regulations
FCC Part 15B (U.S.A.)
Radio Regulations
FCC Part 15C (U.S.A.)
Environmental Certifications
ENERGY STAR® (Worldwide)

Operational Environment
Temperature: 59° - 86° F (15° - 30° C)
Relative Humidity: 10 - 80% (No Condensation)

Printer and Stand Dimensions (H x W x D) and Weight
42" x 39" x 34" Approx. 102 lb.

L24ei Scanner Dimensions (H x W x D) and Weight
With Stand, Basket, and Pallet: 8" x 10" x 41" Approx. 22 lb.

Options
• 2"/3" Roll Holder Set (RH2-28) (needed to support 3" media cores)
• PosterArtist

User-Replaceable Items
• Ink Tank (PFI-030)
• Print Head (PF-06)
• Maintenance Cartridge (MC-31)
• Cutter Blade (CT-08)

What's In The Box
Printer, Stand, Tools and Screws, Power Cord, Print Head, Maintenance Cartridge (Installed), 6 Ink Tanks (55 ml: MBK x 2/BK/C/M/Y), Ethernet Card (built-in), USB 2.0 High-speed Interface, USB Connection Sheet, iWR Service Terms Leaflet, User Manual, Quick Setup Guide, User Software CD for Windows (Printer Driver Utilities), User Registration Card

L24ei SERIES SCANNER SPECIFICATIONS

Scan Speed**
• 24-bit Full Color @ 200 dpi: 1" (per second)
• 8-bit Grayscale and Monochrome @ 200 dpi: 3" (per second)

Scan Modes
• 16.7-million Color RGB (24-bit)
• 256-level Grayscale (8-bit)
• Black and White (1-bit)

Color Space
Normalized RGB

Resolution
600 dpi (optical)

Scan Accuracy*
+/- 0.2%

Maximum Image Width
24"

Maximum Media Width
26"

Maximum Scan Length
109"

Maximum Media Thickness
0.020" (5 mm)

Digital Imaging Technology
Contact Image Sensor (CIS) Technology (SingleSensor Technology Assembly)
• Full width SingleSensor CIS Assembly
• 24-bit RGB digital color image capture
• 8-bit grayscale image capture
• Panchromatic monochrome and black and white
• Bi-directional extra long-life LED light system for optimum object illumination and instant-on scanning capability

Scanner Interface
Scan to USB - USB2 interface
(Flash drive max. size = 128 GB - FAT32)
Copy/Scan to Network - Ethernet interface
(>1 GB Ethernet connection for network configuration)

Operating Environments
10 - 35°C, 35-80% RH, Non-condensing

External Power Supply
100-240 VAC Autosensing +/- 10%, 50-60Hz

Scanner Power Consumption
Scanning: 11.7 W
Standby: .06 W

Compliances
CB, CE, FCC, UL, ENERGY STAR, ICES-003, CUL, S Mark

Dimensions (H x W x D) (with Paper Tray Extended)
5.2" x 36.8" x 9.96"

Stand and Scanner Weight
Approx. 11.6 lb.

What's In The Box?
• L24ei Scanner with Power Cord
• Ethernet Cable
• 2 Mounting Brackets
• CD for ScanApp Lei Software
• Lei Scanner Guide
• Document Return Guide
• Calibration Target
• Feet for Desktop Use
• Two Paper Edge Guides and Paper Refeed Preventers

* Line accuracy repeatability is guaranteed after a user performs necessary adjustment and under the same environmental conditions. Applies to media for line drawing (Plain Paper, Coated Paper, CAD Translucent Matte Film, and CAD Tracing Paper) only.

■ Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients.

■■ The scan rate is proportional across the full range of resolutions supported by the scanner. Quoted top speeds may be limited by the effective bandwidth of the USB 2 and is not guaranteed for all media types.

▲ The quoted scan accuracy may vary depending on the operating environment and the thickness of the media.

Note: The imagePROGRAF TA Series MFP Lei systems contain multiple components, some of which are manufactured by third parties. To the extent that such third-party offerings come with limited warranties, such limited warranties are hereby passed to the purchaser, and Canon shall have no obligation or any liability with respect to such third-party offerings.

Canon



Unit 2 Petersfield Business Park
Bedford Road
Petersfield
Hampshire
GU32 3QA
Tel: 0844 887 0200
Fax: 0844 887 0199
email: support@kewvisum.com



As an ENERGY STAR Partner, Canon U.S.A., Inc. has qualified this model as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. Canon and imagePROGRAF are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output and screen images are simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2020 Canon U.S.A., Inc. All rights reserved.

CSA-20-0473-4742

0520-CSATA20MFPSS-PDF-IH

