

imagePROGRAF TM-200

REDEFINING THE LARGE-FORMAT PRINTER

Ψ.,

Travel THE World BY AIR

nture with MarNaj Travel today and save up to \$500

-



Technology	
FINE (Photolithography Inkjet Nozzle Engine	ering)
Print Resolution (Max.)	
2400 x 1200 dpi	
Line Accuracy* ±0.1% or Less	
Minimum Line Weight** 0.02 mm	
Number of Nozzles	
Matte Black: 5,120 Nozzles	
Other Colors: 2,560 Nozzles per Color	
Droplet Size	
5 Picoliter	
Nozzle Pitch (Head Resolution)	
1200 dpi x Two Rows	
Print Head Swath	
1.07 inch	
Ink Type	
Pigment: Matte Black (MBK), Cyan (C), Mage Yellow (Y), Black (BK)	nta (M),
Ink Tank	
Shipped with Printer: MBK (130 ml) BK, C, M, Replacement: PFI-120 (130 ml) or PFI-320 (30	. Y (90 ml) 00 ml)
Ink Supply Method	
Tubing System with Sub-tanks for Continuous	Ink Supply
Nozzle Recovery System	
Non-firing Nozzle Detection and Compensati	on
Printer Controller	
L-COA PRO	
Printer RAM 2 GB	
Media Feed	
Roll Feed: One Roll, Top-loading, Front Output	t
Media Width	
Roll Feed: 8"-24"(203 mm –610 mm)	
Cut Sheet: 8"-24"(203 mm -610 mm)	
Printable Margins Roll Feed: All Sides: 0.12" (3 mm) or 0" for Bo	

Borderless Printing Widths (Roll Media Only)

8", 10", 12", 14", 16", 17["], 20", 24", B4 (10.12"/257 mm), A3 (11.69"/297 mm), A3+ (12.95"/329 mm), A2 (16.54"/420 mm), B2 (20.28"/515 mm), A1 (23.39"/ 594 mm) Media Cutter

Durable Dual-Blade Rotary Cutter

Media Thickness

0.07 - 0.8 mm

Media Core Sizes 2" and 3" Core Adapters Included

Maximum Roll Outer Diameter

5.9" (150 mm)

Media Output

Basket (Standard)

Printing Software Utilities

Accounting Manager, Apple AirPrint, Canon Print Service, Device Management Console, Direct Print & Share, Free Layout Plus, imagePROGRAF Printer Driver for Windows*/Mac*, Media Configuration Tool, PosterArtist Lite for Windows, Canon PRINT Inkjet Selphy, Easy-Photo PrintEditor,⁺⁺ Optimized Driver for AutoCAD, Free Layout

Operating System

Windows 7 (32/64 bit), Windows 8.1 (32/64 bit), Windows 10 (32/64 bit), Windows Server 2008 R2, (32/64 bit), Windows Server 2012 (64 bit), Windows Server 2012 R2 (64 bit), Windows Server 2016 (64 bit), Macintosh OS X v10.10.5-v10.12x

Print Language

Printer: SGRaster, HP-GL/2, HP RTL, JPEG Interface

Standard (Built-in): USB 2.0 Hi-Speed, 10/100/ 1000Base-T/TX, Wireless LAN (IEEE 802.11 b/g/n) **Acoustic Noise**

Operation: 44 dB (A) or Less Standby: 35 dB (A) or Less Acoustic Power: 6.0Bels or Less

Power Supply AC 100-240V (50-60 Hz)

Power Consumption

Maximum: 69 W or Less Standby: 3.6 W or Less Power Off: 0.3 W or Less (Executive Order Compliant)

Certifications

Electrical Safety Regulations C TUVus (U.S.A.), C TUVus (Canada) Electromagnetic Interface Regulations FCC Part 15B (U.S.A.), IC (Canada) Radio Regulations FCC Part 15C (U.S.A.), IC (Canada) Environmental Certifications ENERGY STAR[®] (Worldwide)

Operational Environment

Temperature: 59° - 86° F (15° - 30° C) Relative Humidity: 10 - 80% (No Condensation)

Printer Dimensions (H x W x D) and Weight

(With Basket Opened)

42" x 38" x 34" Approx. 112 lb.

Package Dimensions (H x W x D) and Weight

With Stand, Basket, and Pallet 38" x 45" x 36" Approx. 187 lb.

Options

• 2"/3" Roll Holder Set (RH2-28)

PosterArtist

User-Replaceable Items

Ink Tank (PFI-120/PFI-320)

- Print Head (PF-06)
- Maintenance Cartridge (MC-31)
- Cutter Blade (CT-08)

What's In The Box

Printer, Basket, Stand, 2"/3" Core Media Spool (Adapt-Printer, Basket, Stand, 27/3° Core Media Spool (Adapters Included), Power Cord, Tools and Screws, Print Head, Maintenance Cartridge (Installed), 5 Ink Tanks (130 ml: MBK, 90 ml: BK/C/M/Y), Sample Heavyweight Coated Paper (A2/2 Sheets), Ethernet Card (built-in), USB 2.0 High-speed Interface, USB Connection Sheet, iWR Service Terms Leaflet, User Maxuel Quick Setur Guide Liker Software CD User Manual, Quick Setup Guide, User Software CD for Windows (Printer Driver Utilities), PosterArtist Lite CD, User Registration Card

* Line accuracy repeatability is guaranteed after a user performs necessary adjustment and under the same environmental conditions. Applies to media for line drawing (Plain Paper, Coated Paper, CAD Translucent Matte Film, and CAD Tracing Paper) only.

** Theoretical value based on data resolution

[†] The maximum printable length varies depending on the application, OS, and RIP used.

⁺⁺ To be supported in December 2018.

 Wireless printing requires a working network with wireless 802.11b/g or 802.11n capability. Wireless performance may vary based on terrain and distance between the printer and wireless network clients



As an ENERGY STAR Partner, Canon U.S.A., Inc. has qualified this model as meeting the ENERGY STAR energy efficiency criteria through an EPA recognized certification body. ENERGY STAR and the ENERGY STAR mark are registered trademarks owned by the U.S. Environmental Protection Agency. Canon and imagePROGRAF are registered trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output and screen images are simulated. Specifications and availability subject to change without notice. Not responsible for typographical errors. ©2018 Canon U.S.A., Inc. All rights reserved

CSA-18-507

0918-CSATM200SS-PDF-IH

ewvisum

Unit 2 Petersfield Business Park Bedford Road Petersfield Hampshire GU32 3QA Tel: 0844 887 0200 Fax: 0844 887 0199 email: support@kewvisum.com



Canon